


**JOINT INVENTORS**

**Atty. Docket No. J-3227**

"EXPRESS MAIL" mailing label No. EL900439715US

Date of Deposit: February 11, 2002

I hereby certify that this paper (or fee) is being deposited with the United States Postal Service "EXPRESS MAIL POST OFFICE TO ADDRESSEE" service under 37 CFR §1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231

  
Graciela Laboy

**APPLICATION FOR  
UNITED STATES LETTERS PATENT**

**SPECIFICATION**

**TO ALL WHOM IT MAY CONCERN:**

Be it known that, BRIAN C. DAIS, a citizen of the United States, residing at 1828 Rockhill Lane, Howell 48843 in the County of Livingston and State of Michigan, ANGELA M. JOHNSON, a citizen of the United States, residing at 1801 Frawley Drive, Sun Prairie 53590 in the County of Dane and State of Wisconsin, LEWIS D. LEE, a citizen of the United States, residing at 8416 N. Birdie Lane, Evansville 53536 in the County of Rock and State of Wisconsin, and PETE D. SCHROEPFER, a citizen of the United States, residing at 2843 Kingston Drive, Madison 53713 in the County of Dane and State of Wisconsin, have invented a new and useful **COOLING CONTAINER HAVING A COOLANT AND PRESSURE RELIEF APPARATUS**, of which the following is a specification.

COOLING CONTAINER HAVING A COOLANT AND  
PRESSURE RELIEF APPARATUS

Technical Field

5           The present invention relates generally to containers and more particularly to a cooling container having a coolant and pressure relief apparatus.

Background Art

10           Cooling containers are used to contain a variety of products and maintain such products at a reduced temperature relative to ambient temperature for a prolonged period of time. An example of a cooling container is disclosed in E. L. Smith U.S. Patent No. 2,526,165, which describes (in connection with FIG. 6 therein) a container having an outer bowl that surrounds an inner bowl wherein the bowls are hermetically sealed to define a chamber therebetween. A suitable refrigerant liquid such as water  
15           is disposed within the chamber. A user places the container into a household freezer for a long enough period of time to freeze the liquid. Thereafter, the user takes the container out of the freezer and may place a product, such as a perishable food item, within the container. The refrigerant liquid is capable of maintaining the food item placed in the container at a temperature below room temperature for a relatively long  
20           period of time.

          Some prior art containers using a coolant or refrigerant within a cavity have included air space within the cavity to allow for expansion of the refrigerant upon freezing. Allowing for such expansion prevents such containers from rupturing. Another strategy to prevent such rupture of a cooling container is disclosed in Hilado  
25           U.S. Patent No. 4,485,636 where the bottom of the cavity is formed by a resilient diaphragm. The diaphragm allows for expansion of the refrigerant by compressing in response to the expanding refrigerant, thereby increasing the volume of the cavity and preventing the walls of the container from breaking as a result of the expanding refrigerant.

30           While numerous prior art containers deal with pressure increases within a cavity due to expansion of refrigerant upon freezing, no known attempts have been made for handling pressure increases resulting from increased heat. It is possible that

5

In accordance with one aspect of the present invention, a container comprises a first container portion and a second container portion joined to the first container portion to define a sealed cavity therebetween. A coolant is disposed within the sealed cavity. The container further comprises a pressure relief apparatus operable to limit pressure in the sealed cavity.

10

According to a further aspect of the present invention, a container comprises a first container portion and a second container portion joined to the first container portion to define a sealed cavity therebetween. A coolant is disposed within the cavity. A joined section joins the first and second container portions. The joined section is operable to limit pressure within the cavity.

15

A further alternative aspect of the present invention comprehends a container comprising a first container portion having a first wall, a base portion and a first rim. A second container portion has a second wall and a second rim. The second rim is joined to the first rim, thereby defining a cavity between the container portions. A gel is disposed within the cavity. A first raised portion, integral with the second wall, joins the second wall to the base portion and is rupturable in response to a first elevated pressure. A second raised portion, also integral with the second wall, also joins the second wall to the base portion and is rupturable at a second elevated pressure greater than the first elevated pressure.

25

FIG. 1 is an isometric view of a container according to the present invention looking down from above;

FIG. 2 is a bottom view of the container of FIG. 1;

30

FIG. 3 is an isometric view of a lid for use with the container of FIG. 1 looking down from above;

FIG. 4A is a sectional view taken generally along the lines 4A-4A of FIG. 2:

FIG. 4B is a sectional view similar to FIG. 4A illustrating rupture of a first connection region;

FIG. 5 is a front elevational view of a container which does not include a second connection region;

5        FIG. 6A is a sectional view similar to FIG. 4A of a second embodiment of a container illustrating a tear-away weld as the pressure relief apparatus;

FIG. 6B is a sectional view similar to FIG. 4A illustrating rupture of the tear-away weld of the container of FIG. 6A;

10       FIG. 7 is an enlarged sectional view similar to FIG. 4A of a third embodiment of a container illustrating a thinned wall portion as the pressure relief apparatus;

FIG. 8 is a sectional view similar to FIG. 4A of a fourth embodiment of a container illustrating a valve as the pressure relief apparatus; and

FIG. 9 is an enlarged full sectional view of a fifth embodiment illustrating an opening as the pressure relief apparatus;

15       FIG. 10 is an isometric view of a sixth embodiment of a container illustrating a different shape of container looking down from above.

#### Description of the Preferred Embodiments

Referring now to FIG. 1, a container 36 defines an interior space 37 for  
20       placement of products therein. Referring also to FIG. 4A, the container 36 includes a first container portion 39 and a second container portion 42. The container portions 39 and 42 are constructed of polypropylene but other suitable materials may be employed. The first container portion 39 includes a first rim 45. The second  
25       container portion 42 includes a second rim 48 wherein the second rim 48 is joined to the first rim 45, thereby defining a sealed cavity 51 between the container portions 39 and 42. The rims 45 and 48 may be joined by any suitable means including ultrasonic welding, spin welding, hot plate welding or by use of an adhesive, but the portions 39 and 42 are preferably joined by vibration welding. Alternatively, the portions 39 and 42 could be joined in a mechanical fashion (not shown), such as by press fitting or  
30       interfitting, such that the portions 39 and 42 are substantially sealed to define the cavity 51. A coolant (not shown) is placed within the sealed cavity 51. The first container portion 39 includes a first base portion 54, and the second container portion

42 includes a second base portion 57. A pressure relief apparatus 58 comprises a joined section 60 (seen also in FIG. 2) that joins the first base portion 54 to the second base portion 57 at first and second connection regions 63 and 66.

Any suitable coolant may be disposed within the cavity 51, but preferably the  
5 coolant is a cross-linked gel having a generally solid structure such that if the gel were heated the gel matrix tends to remain intact allowing only water vapor to escape from the gel matrix. In operation, the container 36 is first placed in a freezer for a long enough time to freeze the gel. Thereafter, a user may take the container 36 out of the freezer and place products within the interior space 37. The frozen gel should  
10 maintain food or other perishable items placed within the interior space 37 of the container 36 within a temperature range between about 10°C to about 15.5°C for about four to about six hours in a room temperature environment. In an above room temperature environment, the time and temperature ranges are affected somewhat depending on the ambient temperature. A preferred formulation of the gel comprises  
15 a mixture of about 98.2% water and a polymer of about 1.8% to about 2.1% solids. The solids include about 80-85% sodium carboxymethylcellulose, roughly 10-16% sodium benzoate and about 4-6% cross-linkers. The gel is available from Progressive Polymer Application of Sheridan, Wyoming and is sold under the trade name UNIGEL. A small amount of paraben (an anti-microbial preservative) is added to the  
20 gel as an additional component of the preferred gel formulation. Of course, other suitable gel formulations may be employed. It should be noted that the container 36 is not limited to use with only perishable food products. Rather, many other products may be kept cool by placement within the container 36. For example, human organs intended for transplant surgery may be placed temporarily therein. Alternatively, a  
25 cosmetic product, beverage or chemical compound may be placed in the container 36.

FIG. 3 illustrates a lid 67 that may be used to seal contents placed within the container 36 in an airtight manner. The lid 67 includes a grasping tab 68 to facilitate removal of the lid 67.

Assembly of the container 36 includes the following steps. The components  
30 of the gel are mixed together at room temperature. While still in a liquid state, the gel is poured into the second container portion 42. The first container portion 39 is placed within the second container portion 42, thereby displacing the gel upwardly

along the walls of the portions 39 and 42 defining the cavity 51. Within several hours, the gel cures such that it assumes a generally solid structure. Thereafter or before curing of the gel, the joined section 60 is vibration welded to join the base portions 54 and 57. Simultaneously, the rims 45 and 48 are also joined together by vibration welding to seal the cavity 51. However, the respective steps of welding the portions 54 and 57 and of welding the rims 45 and 48 could be performed sequentially.

Referring to FIGS. 4A and 4B, the first connection region 63 includes a projection portion 69 integral with the first container portion 39. The projection portion 69 is vibration welded within an opening 72 of the second container portion 42. The opening 72 is preferably about 1/8 inch in diameter. The first connection region 63 is rupturable upon exposure to elevated pressure within the sealed cavity 51. The elevated pressure may result from heating the gel and/or container 36 such as by placement in a microwave oven. Heat developed within the sealed cavity 51 elevates pressure within the sealed cavity 51 forcing the walls of the first and second container portions 39 and 42 to push away from one another. When sufficient elevated pressure is reached, the walls of the first and second container portions 39 and 42 push away from one another with sufficient force to cause separation (rupture) of the first connection region 63. During separation, the base portion 54 carries the projection portion 69 upwardly away from the base portion 57, thereby removing the projection portion 69 out of the opening 72 and exposing the cavity 51 to the opening 72 as illustrated in FIG. 4B. Exposure of the opening 72 allows steam from the heated gel (or other heated coolant in vapor and/or solid form) to escape from the cavity 51. This prevents the walls of the container 36 from rupturing.

It should be noted that the joined section 60 could alternatively join side portions 73a and 73b (FIG. 4A) of the respective first and second container portions 39 and 42 together. However, the joined section 60 preferably joins the base portions 54 and 57. The opening 72 could also be disposed in the first container portion 39. However, the opening is preferably disposed in the second container portion 42 to prevent contamination of product placed within the interior space 37 of the container 36 by the heated gel. The second connection region 66 joins the first and second container portions 39 and 42 together more securely than the first connection region

63 such that when an elevated pressure is reached within the cavity 51, the first connection region 63 ruptures exposing the opening 72 while the second connection region 66 remains intact. The connection region 66 thus prevents possible inversion of the container portion 39, for example as illustrated in FIG. 5. In this regard, once the first connection region 63 ruptures, the cavity 51 is no longer sealed and it is not possible for sufficient pressure to develop within the unsealed cavity to cause rupture of the second connection region 66.

As described above, the first connection region 63 ruptures in response to elevated pressure to limit pressure in the sealed cavity 51. However, the region 63 could be replaced with a region that alternatively limits elevated pressure by rupturing in response to a different parameter, such as an elevated temperature. By way of example only, a region could be employed that melts below the boiling point of the coolant within the cavity 51. Melting of the region exposes the cavity 51 to the ambient surroundings so that pressure in the cavity 51 is limited. For example, the projection portion 69 might be constructed of a material having such a relatively low melting point that the portion 69 melts in response to such temperature, thereby exposing the opening 72 to the cavity 51. Alternatively, the portion 69 might consist of a material that splinters or cracks in response to such temperature, thereby exposing the opening 72. In such a container, the second connection region 66 would not melt or otherwise rupture in response to the elevated temperature, and as in other embodiments described herein, would prevent possible inversion illustrated in FIG. 5.

FIGS. 6A and 6B illustrate a second embodiment wherein elements common to the various embodiments are given like reference numerals. The first connection region 63 is replaced by a tear-away weld 78 connecting the base portions 54 and 57 adjacent the connection region 66. Upon exposure to an elevated pressure, the base portion 54 separates from the base portion 57 such that the portion 54 tears away a part of the portion 57 welded thereto (at the weld 78) to create an opening 84 (seen in FIG. 6B). The newly created opening 84 exposes the cavity 51, thereby preventing undesirable pressure build-up therein. As discussed above, the assembly of the container 36 includes the step of first filling the container portion 42 with gel while the gel is still in a pourable, liquid state. In the first embodiment illustrated in FIGS. 4A and 4B, pouring the liquid gel into the container portion 42 might result in some

spilling or leakage of the gel through the opening 72 in the second container portion 42. The embodiment illustrated in FIGS. 6A and 6B overcomes this problem by employing the tear-away weld 78 that does not require a pre-existing opening (like the opening 72) in the container portion 42. It should be noted that the weld 78 could alternatively create several smaller openings or perforations (not shown) in the base portion 57 rather than the single opening 84.

FIG. 7 illustrates a third embodiment wherein the joined section 60 is replaced by a thinned wall portion 87 preferably disposed in the base portion 57 of the second container portion 42. Exposure to an elevated pressure in the cavity 51 causes the portion 87 to rupture. A connection region (not shown) identical to the connection region 66 could be disposed near the portion 87 in this or any of the following embodiments discussed hereinafter.

FIG. 8 illustrates a fourth embodiment wherein the joined section 60 is replaced by a valve 90 that opens in response to an elevated pressure in the cavity 51 to limit pressure in the cavity 51.

FIG. 9 illustrates a fifth embodiment wherein the joined section 60 is replaced by a small opening 93 disposed in one of the container portions 39 or 42 (but preferably in the base portion 57 of the container portion 42) which prevents pressure rise beyond a certain level. A resilient plug (not shown) made of rubber or other suitable material could be disposed within the opening 93 to prevent contaminants from entering the cavity 51. Such a plug would eject from the opening in response to an elevated pressure in the cavity 51.

FIG. 10 illustrates a sixth embodiment of a square container 96 that incorporates pressure relief apparatus, but which differs from the container 36 in shape. A lid (not shown) of suitable dimension could be placed on the container to seal products placed within the interior space 37. It should be evident from the container 96 of FIG. 10 that many variations of geometric shape and dimension are possible for a container incorporating any of the pressure relief apparatuses illustrated in FIGS. 4A and 4B and FIGS. 6-9.

Numerous modifications to the present invention will be apparent to those skilled in the art in view of the foregoing description. Accordingly, this description is to be construed as illustrative only and is presented for the purpose of enabling those



354223 41355 551005 551015 551025 551035 551045 551055 551065 551075 551085 551095 551105 551115 551125 551135 551145 551155 551165 551175 551185 551195 551205 551215 551225 551235 551245 551255 551265 551275 551285 551295 551305 551315 551325 551335 551345 551355 551365 551375 551385 551395 551405 551415 551425 551435 551445 551455 551465 551475 551485 551495 551505 551515 551525 551535 551545 551555 551565 551575 551585 551595 551605 551615 551625 551635 551645 551655 551665 551675 551685 551695 551705 551715 551725 551735 551745 551755 551765 551775 551785 551795 551805 551815 551825 551835 551845 551855 551865 551875 551885 551895 551905 551915 551925 551935 551945 551955 551965 551975 551985 551995 552005 552015 552025 552035 552045 552055 552065 552075 552085 552095 552105 552115 552125 552135 552145 552155 552165 552175 552185 552195 552205 552215 552225 552235 552245 552255 552265 552275 552285 552295 552305 552315 552325 552335 552345 552355 552365 552375 552385 552395 552405 552415 552425 552435 552445 552455 552465 552475 552485 552495 552505 552515 552525 552535 552545 552555 552565 552575 552585 552595 552605 552615 552625 552635 552645 552655 552665 552675 552685 552695 552705 552715 552725 552735 552745 552755 552765 552775 552785 552795 552805 552815 552825 552835 552845 552855 552865 552875 552885 552895 552905 552915 552925 552935 552945 552955 552965 552975 552985 552995 553005 553015 553025 553035 553045 553055 553065 553075 553085 553095 553105 553115 553125 553135 553145 553155 553165 553175 553185 553195 553205 553215 553225 553235 553245 553255 553265 553275 553285 553295 553305 553315 553325 553335 553345 553355 553365 553375 553385 553395 553405 553415 553425 553435 553445 553455 553465 553475 553485 553495 553505 553515 553525 553535 553545 553555 553565 553575 553585 553595 553605 553615 553625 553635 553645 553655 553665 553675 553685 553695 553705 553715 553725 553735 553745 553755 553765 553775 553785 553795 553805 553815 553825 553835 553845 553855 553865 553875 553885 553895 553905 553915 553925 553935 553945 553955 553965 553975 553985 553995 554005 554015 554025 554035 554045 554055 554065 554075 554085 554095 554105 554115 554125 554135 554145 554155 554165 554175 554185 554195 554205 554215 554225 554235 554245 554255 554265 554275 554285 554295 554305 554315 554325 554335 554345 554355 554365 554375 554385 554395 554405 554415 554425 554435 554445 554455 554465 554475 554485 554495 554505 554515 554525 554535 554545 554555 554565 554575 554585 554595 554605 554615 554625 554635 554645 554655 554665 554675 554685 554695 554705 554715 554725 554735 554745 554755 554765 554775 554785 554795 554805 554815 554825 554835 554845 554855 554865 554875 554885 554895 554905 554915 554925 554935 554945 554955 554965 554975 554985 554995 555005 555015 555025 555035 555045 555055 555065 555075 555085 555095 555105 555115 555125 555135 555145 555155 555165 555175 555185 555195 555205 555215 555225 555235 555245 555255 555265 555275 555285 555295 555305 555315 555325 555335 555345 555355 555365 555375 555385 555395 555405 555415 555425 555435 555445 555455 555465 555475 555485 555495 555505 555515 555525 555535 555545 555555 555565 555575 555585 555595 555605 555615 555625 555635 555645 555655 555665 555675 555685 555695 555705 555715 555725 555735 555745 555755 555765 555775 555785 555795 555805 555815 555825 555835 555845 555855 555865 555875 555885 555895 555905 555915 555925 555935 555945 555955 555965 555975 555985 555995 556005 556015 556025 556035 556045 556055 556065 556075 556085 556095 556105 556115 556125 556135 556145 556155 556165 556175 556185 556195 556205 556215 556225 556235 556245 556255 556265 556275 556285 556295 556305 556315 556325 556335 556345 556355 556365 556375 556385 556395 556405 556415 556425 556435 556445 556455 556465 556475 556485 556495 556505 556515 556525 556535 556545 556555 556565 556575 556585 556595 556605 556615 556625 556635 556645 556655 556665 556675 556685 556695 556705 556715 556725 556735 556745 556755 556765 556775 556785 556795 556805 556815 5568